

Data Sheet—

Tank Accessories

Level Wands

ALL-S level wands are a low cost float style level switch attached to a rigid PVC wand (various lengths available) with a 2" bung fitting and liquid tight that allows you to set the level switch to a desired tank level.

Rigid Suction Assemblies

RST pump suction assemblies come complete with a Kynar foot valve strainer at the end of a rigid PVC tube (various lengths available). Includes a 2" bung fitting and liquid tight, that allows for setting the foot valve to a desired level and securing it's position.

Level Indicators

LI style level indicators use a stainless steel arm and poly float to adjust a visual indicator attached to a 2" bung fitting for a constant product level indication in a 30 or 55 gallon tank.





Models

Level Wands

ALL-S60	60" (152.4cm)
ALL-S42	42" (106.6cm)
ALL-S30	30" (76.2cm)
ALL-S12	12" (30.5cm)

Rigid Suction Assemblies

RSA-KFC1-16	16" (40.6 cm); 3/8" tubing
RSA-KFC1-36	36" (91.4 cm); 3/8" tubing
RSA-KFC1-48	48" (121.9 cm); 3/8" tubing
RSA-KFC2-16	16" (40.6 cm); 1/4" tubing
RSA-KFC2-36	36" (91.4 cm); 1/4" tubing
RSA-KFC2-48	48" (121.9 cm); 1/4" tubing

^{*} Note: Remove tubing connector from any model for 1/4" MNPT connector.

Specifications

- Wand Sch 80 PVC
- Float Polypropylene
- Contact 1-28 VDC / 50mA
- Bung Adapter 2"

Specifications

- Tube Sch 80 PVC
- Foot Valve PVDF
- · Seat Teflon
- · Ball Ceramic
- Tubing Connection Polypropylene
- Bung Adapter 2"

Level Indicators

LI-30	Level indicator for APCT-35 & DCT-30
LI-55	Level indicator for APCT-55, 70 and

DCT-55 tanks

Specifications

- Arm 304SS
- Float Poly
- Bung Adapter 2" Galvanized Steel