

Little Dipper 2

Fluorometer by Turner Designs

PTSA Trace Chemical Control



Key Features

- Accurate In-Line Measurement
- Compact Design
- Quick Release Tee
- Solid State Design
- Simple 4-20mA Output
- Easy Connection to MegaTron Controllers

Application

The Turner Designs Little Dipper 2 in-line fluorometer is a compact sensor designed for monitoring and control of fluorescent dyes in industrial water systems with a single 4-20mA analog output.

Advantage Controls' makes integration simple and convenient with our pre-fab options and no requirement for an external power supply and mA output isolator.

MegaTron and MegaTron XS controllers with a 4-20mA input can power the Little Dipper 2 and provide accurate relay control with standard set point, high/low alarm, feed limit timer and daily max feed for proportional chemical concentration control. Add optional web communications for maximum customer satisfaction and performance.

Build a LD2 Model Number

Model **LD2820**

Optics

A = PTSA optics (1-300 ppb)

Wiring

1 = Standard 55" quick release cable with stripped ends

2 = 55" quick release cable pre-wired to separately order Advantage controller

3 = 72" quick release cable pre-wiring to separately order Advantage controller

Pre-Fab

X = Probe and tee not installed

Y = Probe and tee pre-installed in controller or pre-fab plumbing (must have Advantage controller or pre-fab ordered as separate line item on same order)

Z = Probe and tee pre-installed like option Y plus plug for tee

Specifications

Sensitivity:	<1 ppb typical	Weight:	4.4 ounces (125g)
Power Draw:	0.80 W @ 12 VDC (1.0 W max)	Length:	8.63" (21.9 cm)
Input Voltage:	8-30 VDC	Material:	PVC - Type I
Signal Output:	4-20 mA	Warm Up Time:	5 seconds
Pressure:	0-100 PSI	Temperature:	0-50°C
		Mounting Tee:	1" FNPT PVC

Handheld Testers

LD2-CHECK-A Hand held LD2 fluorometer with PTSA optics

Parts

LD2-2820-505	Calibration cable and power supply
LD2-2820-510	Replacement tee and nut (1" FNPT)
LD2-021-2800	Replacement cable, 4-20mA; 62" (55" usable)
LD2-CABLE-72	Replacement cable, 4-20mA; 72" (66" usable)
LD2-CABLE-180	Replacement cable, 4-20mA, 180"
LD2-CAL-T	Calibration tee with 1" FNPT plugs
LD2-NUT	Replacement nut for LD2 probe
LD2-O-RING	Replacement o-ring
LD2-PLUG	Plug for LD2 tee
LD2-RPK	Plumbing Kit to replace original tee (tee not included)
LD2-TMP	LD2 tee and plug installed in separately ordered pre-fab
PTSA-100	100 ppb PTSA test solution, 1 liter
PTSA-300	300 ppb PTSA test solution, 1 liter
FLUOR-100	100 ppb Fluorescein test solution, 1 liter

Get the Advantage



4700 Harold Abitz Dr
Muskogee, OK 74403
800-743-7431 phone
888-686-6212 fax
www.advantagecontrols.com